

MF 90° ELBOW with a male threaded G1 and a female threaded end G

Fittings with GAS threading
Fittings



MODEL CODE: LZWMF


TECHNICAL DATA SHEET

Connectivity standard:	Internal thread GAS cylindrical ISO 228/1. External thread GAS cylindrical ISO 228/1 Bucchi srl for pipe fittings adopts as standard connection ISO 228/1; in order to improve hydraulic seal has decided to create its own internal regulations, based on a soft conical thread. Therefore it is noted that to ensure the hydraulic seal declared
Material:	Polypropylene (PP)
Color:	Black (RAL 9011)
Operating pressure:	10 bar at 20°C
Max working temperature:	80°C

Torques

Filettature - Threads - Filetts	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"
Serraggio Max materiale PP - Max Tightening PP material - Serrage Max Matériel PP	2 Nm	3 Nm	6 Nm	8 Nm	10 Nm	15 Nm	20 Nm	25 Nm
Serraggio Max materiale PA - Max Tightening PA material - Serrage Max Matériel PA	3 Nm	5 Nm	8 Nm	10 Nm	12 Nm	17 Nm	30 Nm	35 Nm

The maximum tightening torques specified for fittings depend on the compliance of the threads that reference to international specifications on the threads.



MF 90° ELBOW with a male threaded G1 and a female threaded end G

4000 - Outdoor & Gardening

Dimensions

Code	G1	G	L	L(1)	H	H1	E
LZW MF14	1"1/4	1"1/4	21	24,5	72,5	79,5	49,5
LZW MF11	1"1/2	1"1/2	21	24,5	80	88,5	61
LZW MF20	2"	2"	24	28	96,5	106,5	96,5